



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 (AMD Opteron (TM) 280)

SPECint_rate2000 = 37.7
SPECint_rate_base2000 = 35.7

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: Mar-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	107	30.4	2	107	30.4
175.vpr	2	111	29.3	2	107	30.3
176.gcc	2	62.9	40.6	2	62.1	41.1
181.mcf	2	208	20.1	2	165	25.3
186.crafty	2	63.8	36.4	2	58.0	40.0
197.parser	2	120	34.7	2	120	34.7
252.eon	2	54.6	55.3	2	50.1	60.2
253.perlbnk	2	112	37.1	2	112	37.1
254.gap	2	68.9	37.0	2	68.9	37.0
255.vortex	2	77.6	56.8	2	77.5	56.9
256.bzip2	2	122	28.5	2	119	29.3
300.twolf	2	184	37.8	2	155	45.0

Hardware

CPU: AMD Opteron (TM) 280
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB(I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x2048MB PC3200 CL3.0
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
 Compiler: Intel C++ Compiler 8.0 Build 20031211Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
-Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
181.mcf: -fast -QaxN +FDO ONESTEP=yes
186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
-Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
253.perlbnk: basepeak=yes
254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 (AMD Opteron (TM) 280)

SPECint_rate2000 = 37.7
SPECint_rate_base2000 = 35.7

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: Mar-2005

Notes/Tuning Information (Continued)

255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
-Qoption,c,-ip_ninl_max_total_stats=4500 +FDO shlw32M.lib ONESTEP=yes
256.bzip2: -fast -Qunroll2
300.twolf: -fast -arch:SSE2 -Qansi_alias +FDO shlw32M.lib ONESTEP=yes
BIOS Configuration Notes
Node Interleaving Disabled
Other Configuration Notes
The start /b /wait /affinity command is used to bind CPU(s) to processes.