



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p (AMD Opteron (TM) 854)

SPECfp_rate2000 = 99.4
SPECfp_rate_base2000 = 90.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	60.0	124	4	52.2	142
171.swim	4	121	118	4	116	124
172.mgrid	4	100.0	83.5	4	94.9	88.0
173.applu	4	103	94.6	4	87.3	112
177.mesa	4	64.4	101	4	60.9	107
178.galgel	4	89.0	151	4	79.7	169
179.art	4	112	108	4	77.5	156
183.quake	4	87.7	68.8	4	78.2	77.1
187.facerec	4	76.2	116	4	75.9	116
188.amp	4	143	71.3	4	133	76.6
189.lucas	4	95.6	97.1	4	96.3	96.4
191.fma3d	4	134	72.7	4	126	77.3
200.sixtrack	4	136	37.7	4	115	44.6
301.apsi	4	149	81.1	4	145	83.2

Hardware

CPU: AMD Opteron (TM) 854
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
CPU(s) orderable: 1, 2, 4
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 16x2048MB PC3200 CL3.0
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 1
SuSE kernel 2.6.5-7.139-smp
Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.1
AMD Core Math Library 2.5.1
File System: Linux/ext2
System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on
Portability flags:
 178.galgel: -fixedform
Peak tuning:
 168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
              -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
              -IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on
 171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
 172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_a=3:unroll_size=200
              -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2 -WOPT:mem_opnds=on:aggstr=0
 173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
              -LNO:fusion=2:fission=2:full_unroll_size=10000
 177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
              -WOPT:mem_opnds=on +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p (AMD Opteron (TM) 854)

SPECfp_rate2000 = 99.4
SPECfp_rate_base2000 = 90.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```

178.galgel: -Ofast -OPT:fast_complex=on RM_SOURCES=lapak.f90 +ACML
179.art: -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
183.quake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0 -LNO:fusion=2
            -IPA:plimit=1500 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
            -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
            -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on -fno-math-errno
            -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS Configuration Notes
Node Interleaving is Disabled

Other Configuration Notes
Taskset utility used to bind process to CPU(s)