



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN Tomcat K8E (S2865), AMD Opteron (TM) 180

SPECint_rate2000 = 37.3
SPECint_rate_base2000 = 33.2

SPEC license #: 49 | Tested by: AMD, Austin TX | Test date: Sep-2005 | Hardware Avail: Nov-2005 | Software Avail: Aug-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	96.3	33.7	2	96.2	33.8
175.vpr	2	125	26.0	2	117	27.7
176.gcc	2	67.8	37.7	2	67.6	37.7
181.mcf	2	367	11.4	2	237	17.7
186.crafty	2	46.5	49.9	2	45.7	50.7
197.parser	2	164	25.4	2	129	32.3
252.eon	2	51.6	58.5	2	44.9	67.2
253.perlbnk	2	109	38.4	2	99.3	42.1
254.gap	2	78.2	32.6	2	74.3	34.3
255.vortex	2	79.6	55.4	2	71.0	62.1
256.bzip2	2	115	30.2	2	115	30.2
300.twolf	2	225	30.9	2	176	39.5

Hardware

CPU: AMD Opteron (TM) 180 (939-pin)
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 64KBI + 64KBD/core
Secondary Cache: 1024KB (I+D)/core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x512 MB, DDR400 CL2
Disk Subsystem: IDE, Hitachi 164 GB
Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 9 (SP2) for AMD64
Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.2.1
File System: Linux/reiserfs
System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
C++ programs: -Ofast +FDO

Portability Flags:

176.gcc: srcalt 64bitgcc
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt fmax_errno
253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
-DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
255.vortex: -DSPEC_CPU2000_LP64 srcalt closed_files

Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
175.vpr: -O3 -ipa -m32 +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN Tomcat K8E (S2865), AMD Opteron (TM) 180

SPECint_rate2000 = 37.3
SPECint_rate_base2000 = 33.2

SPEC license #: 49 | Tested by: AMD, Austin TX | Test date: Sep-2005 | Hardware Avail: Nov-2005 | Software Avail: Aug-2005

Notes/Tuning Information (Continued)

```

176.gcc:      -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
181.mcf:      -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty:   -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser:   -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:      -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
              -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
              -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk:  -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak = true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO

```

The tested system can be built using a standard ATX case and an Antec True 550W EPS12V power supply.
All memory slots populated on all CPU(s).
BIOS Version 2.01
Taskset utility used to bind CPU(s) to processes.