



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 336 (3.8 GHz Xeon, 2MB L2 Cache)

SPECint_rate2000 = 23.1

SPECint_rate_base2000 = 22.8

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	171	19.0	2	167	19.4
175.vpr	2	221	14.7	2	211	15.4
176.gcc	2	86.6	29.5	2	86.6	29.5
181.mcf	2	204	20.5	2	204	20.5
186.crafty	2	141	16.4	2	135	17.1
197.parser	2	192	21.7	2	192	21.8
252.eon	2	110	27.3	2	110	27.4
253.perlbnk	2	173	24.2	2	172	24.3
254.gap	2	97.6	26.1	2	96.5	26.4
255.vortex	2	119	37.1	2	119	37.1
256.bzip2	2	183	19.0	2	180	19.4
300.twolf	2	257	27.1	2	256	27.2

Hardware

CPU: Intel Xeon 3.8 GHz (800 MHz system bus)
 CPU MHz: 3800
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 512 MB ECC PC2-3200 Single Rank
 Disk Subsystem: 73GB SCSI 15K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
 Compiler: Intel C/C++ Compiler 9.0 (20050624Z) for 32-bit applications
 Intel Fortran Compiler 9.0 (20050624Z) for 32-bit applications
 Microsoft Visual Studio .NET 13.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.30
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 252.eon: srcalt=stdcpp
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO shlw32M.lib
 C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
 175.vpr: -fast +FDO
 176.gcc: basepeak=yes
 181.mcf: -fast +FDO shlw32M.lib
 186.crafty: -fast -Oa +FDO shlw32M.lib
 197.parser: -fast +FDO
 252.eon: -fast +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 336 (3.8 GHz Xeon, 2MB L2 Cache)

SPECint_rate2000 = 23.1

SPECint_rate_base2000 = 22.8

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -Oa +FDO shlw32M.lib
254.gap:      -fast +FDO
255.vortex   -fast +FDO shlw32M.lib
256.bzip2:   -fast -Qunroll1 -Oa +FDO shlw32M.lib
300.twolf:   -fast +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib: MicroQuill SmartHeap Library 7.1
              www.microquill.com
```