



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro X6DHE/8-G2 Motherboard

SPECint2000 = 1771
SPECint_base2000 = 1777

SPEC license #01176 Tested by: Supermicro Test date: Oct-2005 Hardware Avail: Sep-2005 Software Avail: Apr-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	112	1247	115	1223	
175.vpr	1400	116	1203	116	1205	
176.gcc	1100	52.1	2110	52.1	2110	
181.mcf	1800	95.5	1884	95.5	1884	
186.crafty	1000	72.5	1379	73.0	1370	
197.parser	1800	118	1522	118	1521	
252.eon	1300	55.1	2361	55.3	2353	
253.perlbmk	1800	79.7	2258	80.3	2242	
254.gap	1100	55.5	1980	55.5	1980	
255.vortex	1900	65.1	2919	65.1	2919	
256.bzip2	1500	112	1340	112	1334	
300.twolf	3000	157	1914	157	1913	

Hardware

CPU: Intel Xeon 3.8GHz processor (3.8 GHz, 2MB L2, 800 MHz bus)
 CPU MHz: 3800
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip(Hyper-Threading Technology Disabled)
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 16KBD on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8GB (8x1GB DDR2-400 ECC REG)
 Disk Subsystem: 1 X 40GB IDE
 Other Hardware: N/A

Software

Operating System: Windows 2003 EE SP1
 Compiler: Intel C++ Compiler 9.0 Build 20050430Z (32-bit)
 Microsoft Visual Studio .Net 2003(for libraries)
 SmartHeap Library Version 7.4 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
shlw32M.lib is the SmartHeap Library
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DHE/8-G2 Motherboard

SPECint2000 =	1771
SPECint_base2000 =	1777

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

255.vortex basepeak=yes
256.bzip2: -fast -Oa -Qunroll1 +FDO
300.twolf: -fast -O3 +FDO shlw32M.lib
New 32-bit Windows tools used, approved in May-2005
Tested system was built with SC743S1-R760 Chassis.
Product description located as of:
<http://www.supermicro.com/products/motherboard/Xeon800/E7520/X6DH8-G2.cfm>
The system bus runs at 800MHz