



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G3 (3.0GHz, Dual-Core Intel(R) Xeon(R) processor)

SPECint_rate2000 = 15.7
SPECint_rate_base2000 = 15.6

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	142	11.5	1	143	11.4
175.vpr	1	160	10.1	1	156	10.4
176.gcc	1	67.4	18.9	1	67.4	18.9
181.mcf	1	139	15.1	1	139	15.1
186.crafty	1	91.2	12.7	1	91.4	12.7
197.parser	1	153	13.6	1	152	13.7
252.eon	1	69.6	21.7	1	69.0	21.9
253.perlbnk	1	107	19.5	1	106	19.7
254.gap	1	76.7	16.6	1	75.4	16.9
255.vortex	1	84.7	26.0	1	84.7	26.0
256.bzip2	1	156	11.1	1	156	11.1
300.twolf	1	196	17.7	1	196	17.7

Hardware

CPU: Dual-Core Intel(R) Xeon(R) processor (3.0GHz, 2x2MB L2, 667MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1024MB PC2-3200
Disk Subsystem: 1x72.8GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.0 Build 20050912Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib

Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERL DLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -fast +FDO ONESTEP=yes

175.vpr: -fast +FDO ONESTEP=yes

176.gcc: basepeak = 1

181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -fast +FDO ONESTEP=yes

252.eon: -fast +FDO

253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -fast +FDO ONESTEP=yes

255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G3 (3.0GHz, Dual-Core Intel(R) Xeon(R) processor)

SPECint_rate2000 = 15.7
SPECint_rate_base2000 = 15.6

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

```
256.bzip2: -fast -Oa -Qunroll11 +FDO ONESTEP=yes shlw32M.lib
300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Hyper-Threading Technology disabled
Other Configuration Notes
/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.
```