



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY TX300 S2, 64-bit Intel Xeon 3.80 GHz

SPECfp_rate2000 = 22.6
SPECfp_rate_base2000 = 22.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	118	31.3	2	118	31.3
171.swim	2	252	28.5	2	252	28.5
172.mgrid	2	211	19.8	2	211	19.8
173.applu	2	282	17.3	2	282	17.3
177.mesa	2	165	19.7	2	165	19.7
178.galgel	2	180	37.4	2	180	37.4
179.art	2	159	37.9	2	159	37.9
183.quake	2	83.3	36.2	2	83.3	36.2
187.facerec	2	170	25.9	2	170	25.9
188.amp	2	349	14.6	2	349	14.6
189.lucas	2	214	21.7	2	214	21.7
191.fma3d	2	280	17.4	2	280	17.4
200.sixtrack	2	230	11.1	2	230	11.1
301.apsi	2	327	18.5	2	327	18.5

Hardware

CPU: 64-bit Intel Xeon processor 3.8GHz, 2MB L2, 800MHz system bus
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x512 MB DDRII-RAM PC2-3200R
Disk Subsystem: Fujitsu MAS3184NC (U320, 15krpm)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C and Fortran Compiler 9.0
Build 20050722Z (for 32-bit applications)
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries)
SmartHeap Library Version 7.4
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

178.galgel: -FI /F32000000

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO shlw32M.lib
for C programs: -fast +FDO shlw32M.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY TX300 S2, 64-bit Intel Xeon 3.80 GHz

SPECfp_rate2000 = 22.6

SPECfp_rate_base2000 = 22.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>