



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEQUEST 480

SPECint_rate2000 = 509
SPECint_rate_base2000 = 492

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: May-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	32	139	373	32	137	380
175.vpr	32	133	392	32	129	403
176.gcc	32	71.2	573	32	70.9	576
181.mcf	32	85.5	782	32	86.3	774
186.crafty	32	77.8	477	32	75.2	494
197.parser	32	184	362	32	170	394
252.eon	32	61.7	782	32	58.3	828
253.perlbnk	32	134	498	32	128	521
254.gap	32	152	268	32	145	282
255.vortex	32	100	705	32	95.1	742
256.bzip2	32	125	445	32	124	451
300.twolf	32	207	538	32	199	559

Hardware

CPU: Intel Itanium 2
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 32 cores, 32 chips, 1 core/chip
 CPU(s) orderable: 1-32
 Parallel: no
 Primary Cache: 16KBI + 16KBD (on chip) per CPU
 Secondary Cache: 256KB (on chip) per CPU
 L3 Cache: 9.0MB (on chip) per CPU
 Other Cache: N/A
 Memory: 256GB (256x1GB DIMMs)
 Disk Subsystem: Fujitsu MAT3073NC (SCSI Ultra 320)
 Other Hardware: N/A

Software

Operating System: Red Hat Enterprise Linux AS 4
 Compiler: Intel(R) C++ Compiler for Linux 8.1 (Build 20050518)
 MicroQuill SmartHeap Library 7.3 (www.microquill.com)
 File System: ext2
 System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -fast -auto_ilp32 -IPF_fp_relaxed +FDO
 C++ programs: -fast -ansi_alias -IPF_fp_relaxed +FDO

Peak optimization flags:

164.gzip : -O2 -ipo -static -auto_ilp32 -IPF_fp_relaxed
 -IPFflt_eval_method0 -ansi_alias -ftz +FDO
 175.vpr : -O2 -ipo -static -auto_ilp32 -IPF_fp_relaxed
 -IPFflt_eval_method0 -ftz +FDO
 -Qoption,c,-ip_ninl_max_stats=4000
 -Qoption,c,-ip_ninl_max_total_stats=4500
 176.gcc : -O2 -ipo -static -auto_ilp32 -IPF_fp_relaxed
 -IPFflt_eval_method0 +FDO
 181.mcf : -fast -auto_ilp32 -IPF_fp_relaxed
 -IPFflt_eval_method0 -ansi_alias +FDO
 186.crafty : -O2 -ipo -static -auto_ilp32 -IPF_fp_relaxed
 -IPFflt_eval_method0 -ansi_alias -ansi +FDO
 -Qoption,c,-ip_ninl_max_stats=100



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEQUEST 480

SPECint_rate2000 = 509
SPECint_rate_base2000 = 492

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: May-2005

Notes/Tuning Information (Continued)

```

-Option,c,-ip_ninl_max_total_stats=500
197.parser :-fast -auto_ilp32 -IPF_fp_relaxed
-IPFflt_eval_method0 -ansi_alias +FDO
-Option,c,-ip_ninl_min_stats=15
-Option,c,-ip_ninl_max_stats=3200
-Option,c,-ip_ninl_max_total_stats=4000
Extra Libraries: libsmartheap64.a
252.eon :-fast -auto_ilp32 -IPF_fp_relaxed
-IPFflt_eval_method0 -ansi_alias +FDO
-Option,c,-ip_ninl_max_stats=6400
-Option,c,-ip_ninl_max_total_stats=8000
Extra Libraries: libsmartheap64.a
253.perlbnk :-fast -auto_ilp32 -IPF_fp_relaxed
-IPFflt_eval_method0 -ansi_alias +FDO
-Option,c,-ip_ninl_min_stats=1
-Option,c,-ip_ninl_max_stats=800
-Option,c,-ip_ninl_max_total_stats=4000
Extra Libraries: libsmartheap64.a
254.gap :-fast -auto_ilp32 -IPF_fp_relaxed -nolib_inline
-IPFflt_eval_method0 -ansi_alias +FDO
255.vortex :-fast -auto_ilp32 -IPF_fp_relaxed
-IPFflt_eval_method0 +FDO
Extra Libraries: libsmartheap64.a
256.bzip2 :-fast -auto_ilp32 -IPF_fp_relaxed
-IPFflt_eval_method0 -ansi_alias +FDO
-Option,c,-ip_ninl_min_stats=1
-Option,c,-ip_ninl_max_stats=3200
-Option,c,-ip_ninl_max_total_stats=4000
300.twolf :-fast -auto_ilp32 -IPF_fp_relaxed
-IPFflt_eval_method0 +FDO
Extra Libraries: libsmartheap64.a

```

Processes are bound to CPUs using taskset.

Memory system is in "Non Mirror Mode".

Portability Flags:

```

176.gcc : -DSPEC_CPU2000_LP64 -Dalloca=_alloca
186.crafty : -DLINUX_i386
252.eon : -DSPEC_CPU2000_LP64 -DHAS_ERRLIST
253.perlbnk : -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LINUX_IA64
254.gap : -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
-DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
-DSYS_HAS_SIGNAL_PROTO -include unistd.h
255.vortex : -DSPEC_CPU2000_LP64

```