



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D955XBK motherboard(3.73 GHz, Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology)

SPECfp2000 = 2118

SPECfp_base2000 = 2112

SPEC license #: 13 Tested by: Intel(R) Corporation Test date: Oct-2005 Hardware Avail: Apr-2005 Software Avail: Sep-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	53.5	2988	53.6	2987
171.swim	3100	110	2829	109	2832
172.mgrid	1800	107	1680	107	1680
173.applu	2100	119	1759	118	1785
177.mesa	1400	85.3	1642	85.3	1642
178.galgel	2900	73.8	3930	73.8	3929
179.art	2600	48.0	5420	48.0	5420
183.earthquake	1300	42.2	3084	41.2	3159
187.facerec	1900	85.9	2211	85.9	2213
188.ammpp	2200	165	1332	164	1342
189.lucas	2000	82.0	2440	81.9	2441
191.fma3d	2100	124	1695	124	1695
200.sixtrack	1100	149	741	150	734
301.apsi	2600	180	1448	180	1448

Hardware

CPU: Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology(3.73 GHz, 1066 MHz bus)
CPU MHz: 3733
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2MB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 1 GB (2 512MB Micron MT16HTF6464AY-667B3 PC2-5300U-555-11-ED, DDR2-667, CL5-5-5)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: N/A

Software

Operating System: Windows XP Professional SP2
Compiler: Intel(R) C++ and Fortran Compiler 9.0 for 32-bit Build 20050430Z
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for 177.mesa: -fast shlw32M.lib +FDO
Base tuning for 179.art: -fast shlw32M.lib +FDO
Base tuning for 183.earthquake: -fast shlw32M.lib +FDO
Base tuning for 188.ammpp: -fast shlw32M.lib +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.earthquake: -QxP -Oa -Qrcd -Qipo shlw32M.lib +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D955XBK motherboard(3.73 GHz, Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology)

SPECfp2000 = 2118

SPECfp_base2000 = 2112

SPEC license #: 13 | Tested by: Intel(R) Corporation | Test date: Oct-2005 | Hardware Avail: Apr-2005 | Software Avail: Sep-2004

Notes/Tuning Information (Continued)

187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO

188.amp: -fast -Oa +FDO shlw32M.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 10/2005

<http://www.intel.com/products/motherboard/d955xbk/index.htm>

301.apsi: -fast +FDO

The system bus runs at 1066 MHz