



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos G530 (3.8 GHz Intel Xeon processor, 2MB L2, 800MHz system bus)

SPECfp_rate2000 = 21.8

SPECfp_rate_base2000 = 21.7

SPEC license #: 97 Tested by: Acer Incorporated Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	121	30.6	2	121	30.6
171.swim	2	280	25.6	2	281	25.6
172.mgrid	2	210	19.9	2	210	19.8
173.applu	2	292	16.7	2	292	16.7
177.mesa	2	166	19.6	2	166	19.6
178.galgel	2	188	35.8	2	187	36.1
179.art	2	169	35.6	2	169	35.6
183.quake	2	90.3	33.4	2	90.1	33.5
187.facerec	2	174	25.4	2	174	25.4
188.amp	2	353	14.5	2	319	16.0
189.lucas	2	233	19.9	2	229	20.2
191.fma3d	2	289	16.9	2	289	16.9
200.sixtrack	2	231	11.0	2	239	10.7
301.apsi	2	350	17.3	2	349	17.3

Hardware

CPU: Intel Xeon (3.8 GHz, 2MB L2, 800MHz system bus)
 CPU MHz: 3800
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip(Hyper-Threading Technology Enable)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 1GB ECC DDR2-400 SDRAM
 Disk Subsystem: 1 x 146GB 10000RPM U320 SCSI HDD
 Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
 Compiler: Intel C++ 9.0 Build 20050430Z for IA32 and Fortran Compiler 9.0 Build 20050722Z for IA32
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
 shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for all Fortran Programs : -fast -Qansi_alias +FDO
Base tuning for all C Programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
192.fma3d: Approved windowsdp src.alt used
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd -Qprof_gen shlw32M.lib
187.facerec: basepeak=yes
188.amp: -Oa -QxP
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos G530 (3.8 GHz Intel Xeon processor, 2MB L2, 800MHz system bus)

SPECfp_rate2000 = 21.8

SPECfp_rate_base2000 = 21.7

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

189.lucas: -fast -Qprefetch- +FDO

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Enable hardware prefetching and adjacent cache line prefetch BIOS setting

Product description located at <http://www.acer.com>