



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Bull Express5800-140He/140Rd4

SPECfp_rate2000 = 21.4

SPECfp_rate_base2000 = 21.4

SPEC license #: 20 Tested by: Bull Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Oct-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	649	22.9	8	649	22.9
171.swim	8	1732	16.6	8	1732	16.6
172.mgrid	8	906	18.4	8	906	18.4
173.applu	8	4879	3.99	8	4879	3.99
177.mesa	8	209	62.3	8	209	62.3
178.galgel	8	727	37.0	8	727	37.0
179.art	8	907	26.6	8	907	26.6
183.equake	8	540	22.4	8	540	22.4
187.facerec	8	490	36.0	8	490	36.0
188.amp	8	1540	13.3	8	1540	13.3
189.lucas	8	952	19.5	8	952	19.5
191.fma3d	8	638	30.6	8	638	30.6
200.sixtrack	8	297	34.4	8	297	34.4
301.apsi	8	2203	11.0	8	2203	11.0

Hardware

CPU: Intel Xeon MP(3.16GHZ, 1MB L2, 667MHz System bus)
CPU MHz: 3160
FPU: Integrated
CPU(s) enabled: 4 cores, 4 chips, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1 to 4
Parallel: No
Primary Cache: 12 KB (I) micro-ops +16 KB (D) on chip
Secondary Cache: 2*1MB on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2* 512 MB SDRAM DDR2 400 ECC
Disk Subsystem: 73 GB SCSI 10000rpm
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (Build 3790)
Compiler: Intel C/C++ and Fortran Compilers 8.1 for Windows (Build 20051008z)
Microsoft Visual Studio .net 2003 (7.1.3091, for libraries)
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=/Qprof_gen PASS2=/Qprof_use
Base tuning:
C programs: -fast -Qansi_alias +FDO
Fortran programs: -fast -Qansi_alias +FDO
```

```
Portability
178.galgel: -FI /F32000000
```

```
Peak tuning flags
same as baseline (basepeak=true set globally)
```

This result was measured with 32-bit binaries using the 32-bit version of the operating system.
Express5800-140He and 140Rd4 are electronically equivalent
Measured on Express5800-120Rd4