



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM

IBM eServer 326m, 2.4 GHz Dual Core AMD Opteron(tm) Processor 280

SPECint_rate2000 = 75.1

SPECint_rate_base2000 = 66.1

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2005 | Hardware Avail: Nov-2005 | Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	96.6	67.3	4	96.7	67.2
175.vpr	4	124	52.2	4	118	55.1
176.gcc	4	68.1	74.9	4	69.4	73.6
181.mcf	4	342	24.4	4	208	40.1
186.crafty	4	46.8	99.1	4	45.8	101
197.parser	4	167	50.1	4	131	63.6
252.eon	4	53.3	113	4	44.8	135
253.perlbnk	4	113	73.9	4	98.3	84.9
254.gap	4	77.4	66.0	4	73.2	69.7
255.vortex	4	81.7	108	4	73.2	121
256.bzip2	4	113	61.4	4	113	61.4
300.twolf	4	234	59.5	4	180	77.4

Hardware

CPU: Dual Core AMD Opteron(tm) Processor 280
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB (I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024GB PC3200
 Disk Subsystem: SCSI, 36GB 15K RPM
 Other Hardware: None

Software

Operating System: SuSE Linux 9.0 SP2 SLES 64 bit Kernel 2.6.5-7.191-smp (SP2)
 Compiler: PathScale EKO Compiler Suite, Release 2.2.1
 File System: Linux/reiserfs
 System State: Multi-user, run level 3

Notes/Tuning Information

Tested by IBM Corporation

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Base tuning for C programs: -Ofast +FDO

Base tuning for C++ programs: -Ofast +FDO

Portability flags:

186.crafty: -DLINUX_i386

252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64

253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL

-DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64

254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO

-DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64

255.vortex: -DSPEC_CPU2000_LP64

Peak tuning:

164.zip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO

175.vpr: -O3 -ipa -m32 +FDO

176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO

181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO

186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO

197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO

252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM

IBM eServer 326m, 2.4 GHz Dual Core AMD Opteron(tm) Processor 280

SPECint_rate2000 = 75.1

SPECint_rate_base2000 = 66.1

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2005 | Hardware Avail: Nov-2005 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```

-OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exception
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO

```

BIOS Configuration Notes

Node Interleaving Disabled

Other Configuration Notes

Taskset utility used to bind process to CPU(s)