



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEPOWER250 (1650MHz)

SPECfp\_rate2000 = 36.9

SPECfp\_rate\_base2000 = 33.5

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Dec-2005 | Hardware Avail: Feb-2006 | Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	129	28.8	2	122	30.3
171.swim	2	144	49.8	2	89.1	80.8
172.mgrid	2	265	15.8	2	241	17.3
173.applu	2	159	30.6	2	145	33.6
177.mesa	2	153	21.2	2	125	26.0
178.galgel	2	89.6	75.1	2	72.1	93.3
179.art	2	13.0	465	2	12.9	466
183.equake	2	81.4	37.1	2	79.8	37.8
187.facerec	2	92.7	47.5	2	91.0	48.4
188.amp	2	228	22.4	2	194	26.3
189.lucas	2	258	18.0	2	258	18.0
191.fma3d	2	267	18.2	2	269	18.1
200.sixtrack	2	181	14.1	2	181	14.1
301.apsi	2	245	24.6	2	245	24.6

### Hardware

CPU: SPARC64 V  
 CPU MHz: 1650  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
 CPU(s) orderable: 1 to 2 (increments of 1)  
 Parallel: None  
 Primary Cache: 128KBI + 128KBD on chip  
 Secondary Cache: 3MB(I+D) on chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 8GB (1GB x 8)  
 Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)  
 Other Hardware: None

### Software

Operating System: Solaris 10  
 Compiler: Sun Studio 11  
 File System: ufs  
 System State: multi user

## Notes/Tuning Information

```
FDO: (for Sun Studio 11)
fdo_pre0=rm -rf ./feedback.profile ./SunWS_cache
PASS1=-xprofile=collect:./feedback
PASS2=-xprofile=use:./feedback
```

```
Floating point base flags:
(using Fortran compiler of Sun Studio 11)
-fast -xtarget=ultra3cu -xipo=2 ONESTEP=yes FDO
(using C compiler of Sun Studio 11)
-fast -xtarget=ultra3 -xipo=2 ONESTEP=yes FDO
```

```
Floating point peak flags:
(using Fortran compiler of Sun Studio 11)
168.wupwise: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
              -xipo=1 -Qoption iropt -Ainline:inc=800:cp=1 ONESTEP=yes FDO
171.swim:    -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEPOWER250 (1650MHz)

SPECfp\_rate2000 = 36.9  
SPECfp\_rate\_base2000 = 33.5

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Dec-2005 | Hardware Avail: Feb-2006 | Software Avail: Nov-2005

## Notes/Tuning Information (Continued)

```

-xprefetch=latx:2.8 -Qoption iropt
-Ainline:cs=700,-Atile:skewp:b19 -xpad=common:1500
172.mgrid: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
           -stackvar -xipo=2 -xpad=common:800 -xprefetch=latx:1.6
           ONESTEP=yes FDO
173.applu: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
           -stackvar -xipo=2 -Qoption cg -Qlp=1-av=192-t=4-fa=1-fl=0
           -Qoption iropt -Aujam:inner=g ONESTEP=yes FDO
178.galgel: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
            -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90 ONESTEP=yes FDO
187.facerec: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
            -xprefetch=latx:1.6 ONESTEP=yes FDO
189.lucas: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
            -stackvar -xipo=2 ONESTEP=yes FDO
191.fma3d: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
            -xipo=2 ONESTEP=yes FDO
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes

```

(using C compiler of Sun Studio 11)

```

177.mesa: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
          -xchip=ultra2 -xalias_level=strong -xipo=2 -xrestrict
          ONESTEP=yes FDO
179.art: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
          -xipo=2 ONESTEP=yes FDO
183.quake: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
            -xalias_level=strong -W2,-whole -Wc,-Qms_pipe-pref,
            -Qlp=1-av=512-t=6-fa=1-fl=1 ONESTEP=yes FDO
188.ammp: -fast -xalias_level=std -xipo=2 ONESTEP=yes FDO

```

Portability:

178.galgel: -e -fixed

System Tunables:

(for /etc/system)

```

set consistent_coloring=1
set tune_t_fsflushr=86400
set autoup=86400

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Sun Studio 11, posted at URL <http://www.sun.com/software/products/studio/index.xml> was used for this submission.