



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R510 Mk2 (3.0 GHz Intel Xeon processor, 2MB L2, 800MHz system bus)

SPECfp_rate2000 = 29.9

SPECfp_rate_base2000 = 29.7

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Dec-2005 | Hardware Avail: Jan-2006 | Software Avail: Jul-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	77.7	47.8	2	77.7	47.8
171.swim	2	281	25.6	2	281	25.6
172.mgrid	2	180	23.2	2	180	23.2
173.applu	2	221	22.0	2	221	22.0
177.mesa	2	107	30.4	2	107	30.4
178.galgel	2	105	64.3	2	105	64.2
179.art	2	85.5	70.5	2	85.5	70.5
183.quake	2	84.6	35.7	2	84.5	35.7
187.facerec	2	126	34.9	2	126	34.9
188.amp	2	232	22.0	2	213	24.0
189.lucas	2	188	24.7	2	188	24.7
191.fma3d	2	211	23.1	2	211	23.1
200.sixtrack	2	184	13.9	2	184	13.9
301.apsi	2	265	22.7	2	264	22.8

Hardware

CPU: Intel Xeon (3.0 GHz, 2MB L2, 800MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology Disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 6 x 512MB ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 160GB 7200RPM SATA HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler: Intel C++ 9.0 Build 20050430Z for IA32 and Fortran Compiler 9.0 Build 20050722Z for IA32
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for all Fortran Programs : -fast -Qansi_alias +FDO
Base tuning for all C Programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
192.fma3d: Approved windowsdp src.alt used
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd -Qprof_gen shlw32M.lib
187.facerec: basepeak=yes
188.amp: -Oa -QxP
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R510 Mk2 (3.0 GHz Intel Xeon processor, 2MB L2, 800MHz system bus)

SPECfp_rate2000 = 29.9

SPECfp_rate_base2000 = 29.7

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Dec-2005 | Hardware Avail: Jan-2006 | Software Avail: Jul-2005

Notes/Tuning Information (Continued)

189.lucas: -fast -Qprefetch- +FDO

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Enable hardware prefetching and adjacent cache line prefetch BIOS setting

Product description located at <http://www.acer.com>