



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN Tomcat K8E (S2865), AMD Opteron(TM) 185

SPECfp2000 = 1884
SPECfp_base2000 = 1733

SPEC license #: 49 Tested by: AMD Austin, Texas Test date: Feb-2006 Hardware Avail: Mar-2006 Software Avail: Sep-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	59.0	2710	59.1	2708	
171.swim	3100	138	2244	135	2290	
172.mgrid	1800	113	1600	113	1599	
173.applu	2100	145	1450	134	1563	
177.mesa	1400	139	1007	68.8	2034	
178.galgel	2900	102	2848	94.2	3079	
179.art	2600	60.3	4312	60.3	4312	
183.earth	1300	77.6	1674	76.3	1704	
187.facerec	1900	96.4	1971	96.4	1971	
188.amp	2200	182	1210	156	1408	
189.lucas	2000	107	1874	95.9	2085	
191.fma3d	2100	138	1518	136	1543	
200.sixtrack	1100	139	791	139	792	
301.apsi	2600	185	1407	185	1403	

Hardware

CPU: AMD Opteron(TM) 185 (939-pin)
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: no
Primary Cache: 64KBI + 64KBD (on chip) per core
Secondary Cache: 1024KB (I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 2x512MB, DDR400 CL2
Disk Subsystem: SATA, 250 GB
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise edition SP1 (32-bit)
Compiler: Intel C++ 9.0 build 20050912Z for IA32, Intel Fortran 9.0 build 20050912Z for IA32, Microsoft Visual Studio .NET 7.0.9466 (libraries) PGI Fortran compiler 6.0-5 for Windows XP, PGI C compiler 6.0-5 for Windows XP, ACML Version 2.5.3 (bundled with PGI 6.0-5)
File System: NTFS
System State: default

Notes/Tuning Information

```
+FDO:
    icl, ifort : PASS1=-Qprof_gen PASS2=-Qprof_use
    pgf90      : PASS1=-Mpfi      PASS2=-Mpfo
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran 90 compiler.
pgcc is the PGI C compiler.
ONESTEP is set to 1 for every compile with the PGI compilers.
Portability:
178.galgel: -Mfixed
Baseline: C : pgcc -fastsse -Mipa=fast,inline
Baseline: Fortran: pgf90 -fastsse -Mipa=fast,inline +FDO
Peak tuning:
168.wupwise: pgf90 -fastsse -Mipa=fast,inline -Mvect
171.swim: ifort -Qipo -O3 -QaxN -QxW -Qunroll0 +FDO
172.mgrid: pgf90 -fastsse -Mipa=fast,inline
173.applu: ifort -Qipo -O3 -QaxN -QxW -auto +FDO
177.mesa: icl -Qipo -QxW -Qunroll1 -Qansi_alias +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN Tomcat K8E (S2865), AMD Opteron(TM) 185

SPECfp2000 = 1884
SPECfp_base2000 = 1733

SPEC license #: 49 | Tested by: AMD Austin, Texas | Test date: Feb-2006 | Hardware Avail: Mar-2006 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

```

-Option,c,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
178.galgel:          pgf90  -fastsse -Mipa=fast,safe -Munix -lacml
                    RM_SOURCES=lapak.f90
179.art:             pgcc    basepeak=yes
183.quake:           icl     -O3 -Qipo -QxW +FDO
187.facerec:         pgf90  basepeak=1
188.ampp:            icl     -Oa  -QxW  -Zp4 -Qansi_alias
189.lucas:           ifort   -Qipo -QxW -Qunroll1
191.fma3d:           pgf90  -Mipa=fast,inline -fastsse -Mnovect +FDO
200.sixtrack:        pgf90  -fastsse -Mipa=fast,inline
301.apsi:            pgf90  -fastsse -Mipa=fast,inline

```

Corsair CMX512-3200XL memory used in Dual Channel configuration.

Memory timings manually set in BIOS: Command Rate=1T

BIOS rev 3.01

The tested system can be assembled using a standard ATX case and an Antec True 550 watt EPS12V Power Supply.

/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.