



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon 5080 processor, 3.73 GHz

SPECint\_rate2000 = 81.2

SPECint\_rate\_base2000 = 81.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jun-2006 | Software Avail: Oct-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	8	174	74.5	8	174	74.5
175.vpr	8	252	51.6	8	252	51.6
176.gcc	8	90.0	113	8	90.0	113
181.mcf	8	420	39.7	8	420	39.7
186.crafy	8	143	65.1	8	143	65.1
197.parser	8	202	82.8	8	202	82.8
252.eon	8	110	109	8	110	109
253.perlbnk	8	175	95.6	8	175	95.6
254.gap	8	114	89.5	8	114	89.5
255.vortex	8	130	135	8	130	135
256.bzip2	8	209	66.5	8	209	66.5
300.twolf	8	267	104	8	267	104

### Hardware

CPU: Intel Xeon 5080 processor (3.73 GHz, 2x2MB SLC, 1066 MHz system bus)  
CPU MHz: 3733  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12k micro-ops I + 16KBD on chip, per core  
Secondary Cache: 2048KB(I+D) on chip, per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1024 MB DDRII-RAM PC2-4200F (CAS 4-4-4)  
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1  
Compiler: Intel C++ Compiler 9.0  
Build 20051020Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 8.0  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafy: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### Base tuning flags

for C programs: -fast +FDO shlw32M.lib  
for C++ programs: -fast -Qcxx\_features +FDO shlw32M.lib

### Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 1066 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX300 S3, Intel Xeon 5080 processor, 3.73 GHz

SPECint\_rate2000 = 81.2

SPECint\_rate\_base2000 = 81.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jun-2006 | Software Avail: Oct-2005

## Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>