



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL25p (AMD Opteron (TM) 285)

SPECint\_rate2000 = 39.7  
SPECint\_rate\_base2000 = 35.5

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2006 Hardware Avail: Mar-2006 Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	89.1	36.4	2	89.0	36.5
175.vpr	2	120	27.2	2	113	28.7
176.gcc	2	62.8	40.7	2	63.8	40.0
181.mcf	2	338	12.3	2	211	19.8
186.crafty	2	43.4	53.4	2	42.2	55.0
197.parser	2	155	27.0	2	121	34.6
252.eon	2	48.8	61.8	2	42.0	71.8
253.perlbnk	2	103	40.5	2	92.0	45.4
254.gap	2	69.9	36.5	2	71.4	35.7
255.vortex	2	74.4	59.2	2	69.4	63.5
256.bzip2	2	108	32.3	2	108	32.3
300.twolf	2	221	31.6	2	172	40.4

### Hardware

CPU: AMD Opteron (TM) 285  
CPU MHz: 2600  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 64KBI + 64KBD (on chip) per core  
Secondary Cache: 1024KB(I+D) (on chip) per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4x2048MB PC3200 CL3.0  
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI  
Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 3  
SuSE kernel 2.6.5-7.244-smp  
Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.3  
File System: Linux/ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -Ofast +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
              -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
           -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64
Peak tuning:
 164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
 186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
 197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
 252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
           -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL25p (AMD Opteron (TM) 285)

SPECint\_rate2000 = 39.7  
SPECint\_rate\_base2000 = 35.5

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2006 Hardware Avail: Mar-2006 Software Avail: Jan-2006

## Notes/Tuning Information (Continued)

```

-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO

```

### BIOS Configuration Notes

Node Interleaving Disabled

### Other Configuration Notes

Taskset utility used to bind process to CPU(s)