



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL25p (AMD Opteron (TM) 285)

SPECint\_rate2000 = 39.2  
SPECint\_rate\_base2000 = 37.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2006 Hardware Avail: Mar-2006 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	100	32.5	2	100	32.5
175.vpr	2	109	29.9	2	105	30.9
176.gcc	2	59.8	42.7	2	59.3	43.0
181.mcf	2	220	19.0	2	174	24.0
186.crafty	2	59.8	38.8	2	54.6	42.5
197.parser	2	115	36.2	2	115	36.2
252.eon	2	50.8	59.4	2	46.3	65.1
253.perlbnk	2	105	39.9	2	105	39.9
254.gap	2	66.7	38.3	2	66.7	38.3
255.vortex	2	75.3	58.5	2	75.0	58.8
256.bzip2	2	118	29.4	2	118	29.6
300.twolf	2	178	39.1	2	145	47.9

### Hardware

CPU: AMD Opteron (TM) 285  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB(I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x2048MB PC3200 CL3.0  
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI  
 Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise SP1  
 Compiler: Intel C++ Compiler 8.0 Build 20040318Z  
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
 MicroQuill Smartheap Library 7.0  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
-Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
181.mcf: -fast -QaxN +FDO ONESTEP=yes
186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
-Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
253.perlbnk: basepeak=yes
254.gap: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL25p (AMD Opteron (TM) 285)

SPECint\_rate2000 = 39.2  
SPECint\_rate\_base2000 = 37.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2006 Hardware Avail: Mar-2006 Software Avail: Nov-2005

## Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
            -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO shlw32M.lib ONESTEP=yes
256.bzip2:  -fast -Qunroll2
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO shlw32M.lib ONESTEP=yes
```

BIOS Configuration Notes  
Node Interleaving Disabled

Other Configuration Notes  
The start /b /wait /affinity command is used to bind CPU(s) to processes.