



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5050 processor, 3.0 GHz

SPECfp_rate2000 = 44.6

SPECfp_rate_base2000 = 44.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Apr-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	119	62.4	4	119	62.4
171.swim	4	467	30.8	4	467	30.8
172.mgrid	4	294	28.4	4	294	28.4
173.applu	4	325	29.9	4	325	29.9
177.mesa	4	92.7	70.1	4	92.7	70.1
178.galgel	4	123	109	4	123	109
179.art	4	104	116	4	104	116
183.quake	4	211	28.5	4	211	28.5
187.facerec	4	178	49.7	4	178	49.7
188.amp	4	219	46.5	4	219	46.5
189.lucas	4	303	30.6	4	303	30.6
191.fma3d	4	279	34.9	4	279	34.9
200.sixtrack	4	187	27.3	4	187	27.3
301.apsi	4	273	44.1	4	273	44.1

Hardware

CPU: Intel Xeon 5050 processor (3.0 GHz, 2x2MB L2, 667 MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDRII-RAM PC2-4200F (CAS 4-4-4)
Disk Subsystem: Seagate ST936701SS (SAS, 10krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext3
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5050 processor, 3.0 GHz

SPECfp_rate2000 = 44.6

SPECfp_rate_base2000 = 44.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Apr-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 667 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>