



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System x 3950 (Intel Xeon processor 7030, 2MB L2 Cache)

SPECint_rate2000 = 87.0

SPECint_rate_base2000 = 83.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Feb-2006 | Hardware Avail: Apr-2006 | Software Avail: Dec-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	371	70.1	16	264	98.3
175.vpr	16	493	52.7	16	478	54.3
176.gcc	16	209	97.9	16	209	97.9
181.mcf	16	817	40.9	16	817	40.9
186.crafty	16	207	89.8	16	206	90.0
197.parser	16	316	106	16	315	106
252.eon	16	156	155	16	156	154
253.perlbnk	16	248	135	16	248	135
254.gap	16	553	36.9	16	430	47.4
255.vortex	16	191	184	16	190	185
256.bzip2	16	382	72.9	16	423	65.8
300.twolf	16	726	76.7	16	729	76.4

Hardware

CPU: Intel Xeon processor 7030 (667 MHz system bus)
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology enabled)
 CPU(s) orderable: 1,2,3,4
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 16KB(D) (on chip) per core
 Secondary Cache: 2048KB(I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16 x 2048 MB ECC PC2-3200 Dual Rank
 Disk Subsystem: 73GB SAS 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
 Compiler: Intel C/C++ Compiler 9.0 (20051130Z) for 32-bit applications
 Microsoft Visual Studio .NET 13.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.30
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO shlw32m.lib
 C++: -fast -Qcxx_features +FDO shlw32m.lib

PEAK TUNING

164.gzip: -fast +FDO
 175.vpr: -fast +FDO
 176.gcc: basepeak=yes
 181.mcf: -fast +FDO shlw32m.lib
 186.crafty: -fast -Oa +FDO shlw32m.lib
 197.parser: -fast +FDO
 252.eon: -fast +FDO shlw32m.lib
 253.perlbnk: -fast -Oa +FDO shlw32m.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System x 3950 (Intel Xeon processor 7030, 2MB L2 Cache)

SPECint_rate2000 = 87.0

SPECint_rate_base2000 = 83.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Feb-2006 | Hardware Avail: Apr-2006 | Software Avail: Dec-2005

Notes/Tuning Information (Continued)

254.gap: -fast +FDO
255.vortex -fast +FDO shlw32M.lib
256.bzip2: -fast -Qunroll11 -Oa +FDO shlw32M.lib
300.twolf: -fast +FDO shlw32M.lib

EXTRA LIBRARIES

shlw32M.lib: MicroQuill SmartHeap Library 7.3
www.microquill.com

This result was measured on the IBM System X 3850
The System X 3850 and System X 3950 are electronically equivalent.