



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon 5110 processor, 1.60 GHz

SPECfp\_rate2000 = 31.5

SPECfp\_rate\_base2000 = 31.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	78.7	47.2	2	78.7	47.2
171.swim	2	264	27.3	2	264	27.3
172.mgrid	2	184	22.7	2	184	22.7
173.applu	2	198	24.6	2	198	24.6
177.mesa	2	84.8	38.3	2	84.8	38.3
178.galgel	2	92.8	72.5	2	92.8	72.5
179.art	2	69.3	87.0	2	69.3	87.0
183.quake	2	109	27.8	2	109	27.8
187.facerec	2	119	37.1	2	119	37.1
188.amp	2	198	25.8	2	198	25.8
189.lucas	2	186	24.9	2	186	24.9
191.fma3d	2	198	24.7	2	198	24.7
200.sixtrack	2	183	14.0	2	183	14.0
301.apsi	2	257	23.5	2	257	23.5

### Hardware

CPU: Intel Xeon 5110 processor (1.60 GHz, 4MB L2, 1066 MHz system bus)  
CPU MHz: 1600  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 32KBI + 32KBD on chip, per core  
Secondary Cache: 4096KB(I+D) on chip, shared  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1GB DDRII-RAM PC2-4200F (CAS 4-4-4)  
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)  
Other Hardware: none

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3  
Kernel 2.6.5-7.244-smp on an x86\_64  
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T  
Build 20060120 (for 64-bit applications)  
File System: ext3  
System State: Multi-user run level 3

## Notes/Tuning Information

### GENERAL

+FDO implies feedback-directed optimization  
PASS1: -prof\_gen PASS2: -prof\_use

### Optimization flags

ONESTEP=yes set for all benchmarks

### Portability flags

-DSPEC\_CPU2000\_LP64 applied to all benchmarks  
178.galgel: -FI for fixed-format Fortran

### Base tuning flags

for Fortran and C programs: -fast +FDO

### Peak tuning flags

same as baseline (basepeak=true set globally)



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX200 S3, Intel Xeon 5110 processor, 1.60 GHz

SPECfp\_rate2000 = 31.5

SPECfp\_rate\_base2000 = 31.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

## Notes/Tuning Information (Continued)

The system bus runs at 1066 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>