



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML370 G5 (3.0GHz, Intel Xeon processor 5160)

SPECfp2000 = **3048**
SPECfp_base2000 = **2803**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: May-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	38.5	4160	38.5	4160
171.swim	3100	108	2865	105	2951
172.mgrid	1800	91.6	1965	75.4	2389
173.applu	2100	96.1	2185	70.3	2987
177.mesa	1400	45.2	3095	41.5	3375
178.galgel	2900	40.8	7100	40.8	7100
179.art	2600	22.0	11823	22.0	11823
183.quake	1300	56.7	2292	45.6	2850
187.facerec	1900	62.5	3042	47.1	4031
188.amp	2200	101	2169	101	2169
189.lucas	2000	93.3	2145	92.6	2159
191.fma3d	2100	96.7	2172	96.7	2172
200.sixtrack	1100	95.9	1147	95.9	1147
301.apsi	2600	151	1720	144	1800

Hardware

CPU: Intel Xeon processor 5160 (3.0GHz, 4MB L2 shared, 1333MHz bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32KB (I) + 32KB (D) (on chip) per core
 Secondary Cache: 4096KB(I+D) (on chip) shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2048MB PC2-5300F
 Disk Subsystem: 1x36GB 10K SAS
 Other Hardware:

Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD64/EM64T, Update 3 Kernel 2.6.9-34.EL
 Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
 Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
 PathScale EKOPath(TM) Compiler Suite, Release 2.4
 File System: ext2
 System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch Ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML370 G5 (3.0GHz, Intel Xeon processor 5160)

SPECfp2000 = 3048
SPECfp_base2000 = 2803

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```

177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.equake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t
188.ammp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t

```

BIOS Configuration Notes

Power Regulator set to Static High