



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1950 (Intel Xeon processor 5060, 3.20GHz)

SPECfp_rate2000 = 61.9

SPECfp_rate_base2000 = 61.9

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	80.7	92.0	4	80.7	92.0
171.swim	4	295	48.8	4	295	48.8
172.mgrid	4	191	43.6	4	191	43.6
173.applu	4	212	46.0	4	212	46.0
177.mesa	4	82.6	78.7	4	82.6	78.7
178.galgel	4	99.8	135	4	99.8	135
179.art	4	58.4	207	4	58.4	207
183.equake	4	130	46.6	4	130	46.6
187.facerec	4	122	72.0	4	122	72.0
188.amp	4	188	54.2	4	188	54.2
189.lucas	4	191	48.7	4	191	48.7
191.fma3d	4	207	47.0	4	207	47.0
200.sixtrack	4	172	29.7	4	172	29.7
301.apsi	4	244	49.5	4	244	49.5

Hardware

CPU: Intel Xeon processor 5060 (1066MHz system bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1GB 533MHz ECC CL4 DDR2 FB-DIMM
Disk Subsystem: 1 x 80GB SATA 7200 RPM
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T Builds 20060120 and 20051201
File System: ext3
System State: Runlevel 3

Notes/Tuning Information

GENERAL

ONESTEP=yes for all benchmarks

+FDO implies feedback-directed optimization PASS1: -prof_gen PASS2: -prof_use

PORTABILITY FLAGS

-DSPEC_CPU2000_LP64 applied to all benchmarks

178.galgel: -FI for fixed-format Fortran

BASE TUNING

Baseline optimizations for C and Fortran: -fast +FDO

PEAK TUNING

basepeak=yes set for all benchmarks

BIOS SETTINGS

Snoop Filter enabled in BIOS