



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1950 (Intel Xeon processor 5110, 1.60GHz)

SPECint_rate2000 = 72.1

SPECint_rate_base2000 = 72.0

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	143	45.4	4	144	45.3
175.vpr	4	123	52.7	4	121	53.6
176.gcc	4	61.9	82.5	4	61.9	82.5
181.mcf	4	116	71.9	4	116	71.9
186.crafty	4	68.5	67.7	4	68.6	67.6
197.parser	4	144	57.8	4	145	57.6
252.eon	4	62.2	96.9	4	62.2	97.0
253.perlbnk	4	93.7	89.1	4	93.7	89.1
254.gap	4	69.0	73.9	4	68.9	74.1
255.vortex	4	72.2	122	4	72.2	122
256.bzip2	4	130	53.3	4	130	53.5
300.twolf	4	164	84.7	4	164	84.7

Hardware

CPU: Intel Xeon processor 5110 (1066MHz system bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1GB 667MHz ECC CL5 DDR2 FB-DIMM
Disk Subsystem: 1 x 80GB SATA 7200 RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler 9.1 for IA32(20060323Z)
Microsoft Visual Studio .NET 2003(7.1.3088)
MicroQuill SmartHeap Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast +FDO shlw32m.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Oa +FDO shlw32m.lib
197.parser: -fast +FDO
252.eon: -fast +FDO
253.perlbnk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1950 (Intel Xeon processor 5110, 1.60GHz)

SPECint_rate2000 = 72.1

SPECint_rate_base2000 = 72.0

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
254.gap:      -fast +FDO
255.vortex    basepeak=yes
256.bzip2:    -fast -Qunroll11 -Oa +FDO
300.twolf:    basepeak=yes
BIOS SETTINGS
Snoop Filter enabled in BIOS
```