



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1950 (Intel Xeon processor 5150, 2.66GHz)

SPECint2000 = 2764

SPECint_base2000 = 2761

SPEC license #: 55 Tested by: Dell, Round Rock, TX Test date: May-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	84.7	1654	84.7	1653	
175.vpr	1400	69.7	2008	68.7	2039	
176.gcc	1100	36.9	2983	36.9	2983	
181.mcf	1800	45.0	3997	45.0	3997	
186.crafty	1000	41.1	2431	41.2	2428	
197.parser	1800	81.7	2204	81.6	2207	
252.eon	1300	37.3	3488	37.3	3483	
253.perlbmk	1800	55.3	3257	55.3	3257	
254.gap	1100	40.2	2739	40.0	2747	
255.vortex	1900	41.6	4568	41.6	4568	
256.bzip2	1500	70.8	2120	71.0	2114	
300.twolf	3000	97.6	3075	97.6	3075	

Hardware

CPU: Intel Xeon processor 5150 (1333MHz system bus)
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1GB 667MHz ECC CL5 DDR2 FB-DIMM
Disk Subsystem: 1 x 80GB SATA 7200 RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler 9.1 for IA32(20060323Z)
Microsoft Visual Studio .NET 2003(7.1.3088)
MicroQuill SmartHeap Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast +FDO shlw32m.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Oa +FDO shlw32m.lib
197.parser: -fast +FDO
252.eon: -fast +FDO
253.perlbmk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1950 (Intel Xeon processor 5150, 2.66GHz)

SPECint2000 = 2764

SPECint_base2000 = 2761

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

254.gap: -fast +FDO
255.vortex basepeak=yes
256.bzip2: -fast -Qunroll11 -Oa +FDO
300.twolf: basepeak=yes
BIOS SETTINGS
Snoop Filter enabled in BIOS