



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G5 (3.0GHz, Intel Xeon processor 5160)

SPECfp_rate2000 = **82.1**
SPECfp_rate_base2000 = **77.6**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	67.5	110	4	67.5	110
171.swim	4	283	50.9	4	275	52.4
172.mgrid	4	211	39.6	4	209	40.0
173.applu	4	184	53.0	4	136	71.8
177.mesa	4	47.5	137	4	43.1	151
178.galgel	4	70.8	190	4	70.8	190
179.art	4	54.3	222	4	54.3	222
183.quake	4	128	47.2	4	101	59.7
187.facerec	4	85.5	103	4	78.5	112
188.amp	4	121	84.5	4	121	84.5
189.lucas	4	178	52.3	4	176	52.6
191.fma3d	4	163	59.8	4	163	59.8
200.sixtrack	4	98.7	51.7	4	98.7	51.7
301.apsi	4	191	63.1	4	185	65.1

Hardware

CPU: Intel Xeon processor 5160 (3.0GHz, 4MB L2 shared, 1333MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB (I) + 32KB (D) (on chip) per core
Secondary Cache: 4096KB(I+D) (on chip) shared
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB PC2-5300F
Disk Subsystem: 1x36GB 10K SAS
Other Hardware:

Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD/EM64T, Update 3 Kernel 2.6.9-34.ELsmp
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
PathScale EKOPATH(TM) Compiler Suite, Release 2.4
File System: ext2
System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch Ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G5 (3.0GHz, Intel Xeon processor 5160)

SPECfp_rate2000 = 82.1
SPECfp_rate_base2000 = 77.6

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.equake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
          -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
188.ammp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
          Power Regulator set to Static High Performance Mode
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
```

BIOS Configuration Notes