



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G5 (3.73GHz, Intel Xeon processor 5080)

SPECfp2000 = 1966
SPECfp_base2000 = 1959

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	44.4	3606	44.4	3606	
171.swim	3100	117	2646	117	2645	
172.mgrid	1800	113	1599	113	1600	
173.applu	2100	117	1801	117	1801	
177.mesa	1400	86.8	1613	86.3	1622	
178.galgel	2900	76.6	3787	76.6	3787	
179.art	2600	56.4	4608	56.4	4608	
183.quake	1300	44.3	2933	44.3	2933	
187.facerec	1900	114	1666	114	1668	
188.amp	2200	186	1183	180	1225	
189.lucas	2000	114	1760	113	1771	
191.fma3d	2100	130	1615	130	1615	
200.sixtrack	1100	149	737	149	737	
301.apsi	2600	199	1307	199	1307	

Hardware

CPU: Intel Xeon processor 5080 (3.73GHz, 2x2MB L2, 1066MHz bus)
CPU MHz: 3730
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB PC2-5300F dual-rank
Disk Subsystem: 1x36GB 10K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Intel Fortran Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smarheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability flags:
 178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast +FDO ONESTEP=yes
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=1
177.mesa: -fast +FDO ONESTEP=yes
178.galgel: basepeak=1
179.art: basepeak=1
183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes
188.amp: -fast -Qansi_alias +FDO
189.lucas: -fast
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G5 (3.73GHz, Intel Xeon processor 5080)

SPECfp2000 = 1966
SPECfp_base2000 = 1959

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
191.fma3d:    basepeak=1
200.sixtrack: -fast                +FDO
301.apsi:     basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology disabled
Power Regulator set to Static High Performance Mode
```