



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5150 processor, 2.66 GHz

SPECint_rate2000 = 111

SPECint_rate_base2000 = 111

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

250	200	150	100	50	Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
					164.zip	4	87.3	74.4	4	87.3	74.4
					175.vpr	4	81.7	79.5	4	81.7	79.5
					176.gcc	4	44.9	114	4	44.9	114
					181.mcf	4	85.7	97.4	4	85.7	97.4
					186.crafy	4	41.1	113	4	41.1	113
					197.parser	4	91.1	91.7	4	91.1	91.7
					252.eon	4	37.8	159	4	37.8	159
					253.perlbnk	4	58.2	143	4	58.2	143
					254.gap	4	47.7	107	4	47.7	107
					255.vortex	4	48.6	181	4	48.6	181
					256.bzip2	4	88.8	78.4	4	88.8	78.4
					300.twolf	4	98.8	141	4	98.8	141

Hardware

CPU: Intel Xeon 5150 processor (2.66 GHz, 4MB SLC, 1333 MHz system bus)
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDRII-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm, 73GB)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060323Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 1333 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5150 processor, 2.66 GHz

SPECint_rate2000 = 111

SPECint_rate_base2000 = 111

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

BIOS configuration:

Adjacent Sector Prefetch = disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>