



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5160 processor, 3.0 GHz

SPECfp_rate2000 = 46.9

SPECfp_rate_base2000 = 46.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|--------------|-------------|--------------|------------|--------|---------|-------|
| 168.wupwise | 2 | 55.4 | 67.1 | 2 | 55.4 | 67.1 |
| 171.swim | 2 | 207 | 34.8 | 2 | 207 | 34.8 |
| 172.mgrid | 2 | 137 | 30.5 | 2 | 137 | 30.5 |
| 173.applu | 2 | 148 | 33.0 | 2 | 148 | 33.0 |
| 177.mesa | 2 | 47.3 | 68.7 | 2 | 47.3 | 68.7 |
| 178.galgel | 2 | 55.4 | 121 | 2 | 55.4 | 121 |
| 179.art | 2 | 46.3 | 130 | 2 | 46.3 | 130 |
| 183.equake | 2 | 84.6 | 35.6 | 2 | 84.6 | 35.6 |
| 187.facerec | 2 | 78.4 | 56.2 | 2 | 78.4 | 56.2 |
| 188.amp | 2 | 115 | 44.4 | 2 | 115 | 44.4 |
| 189.lucas | 2 | 142 | 32.6 | 2 | 142 | 32.6 |
| 191.fma3d | 2 | 134 | 36.3 | 2 | 134 | 36.3 |
| 200.sixtrack | 2 | 97.5 | 26.2 | 2 | 97.5 | 26.2 |
| 301.apsi | 2 | 168 | 35.8 | 2 | 168 | 35.8 |

Hardware

CPU: Intel Xeon 5160 processor (3.0 GHz, 4MB SLC, 1333 MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1024 MB DDRII-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext2
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5160 processor, 3.0 GHz

SPECfp_rate2000 = 46.9

SPECfp_rate_base2000 = 46.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>