



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Acer Altos R720 (2.66 GHz Intel Xeon Processor 5150)

SPECfp_rate2000 = 77.5
SPECfp_rate_base2000 = 77.5

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Jul-2006 | Hardware Avail: Jun-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	67.6	110	4	67.6	110
171.swim	4	267	53.8	4	267	53.8
172.mgrid	4	172	48.6	4	172	48.6
173.applu	4	184	53.0	4	184	53.0
177.mesa	4	53.2	122	4	53.2	122
178.galgel	4	65.0	207	4	65.0	207
179.art	4	54.6	221	4	54.6	221
183.equake	4	128	47.1	4	128	47.1
187.facerec	4	90.8	97.0	4	90.8	97.0
188.amp	4	128	79.8	4	128	79.8
189.lucas	4	172	53.8	4	172	53.8
191.fma3d	4	166	58.7	4	166	58.7
200.sixtrack	4	110	46.4	4	110	46.4
301.apsi	4	194	62.2	4	194	62.2

Hardware

CPU: Intel Xeon Processor 5150 (2.66 GHz, 4MB L2, 1333MHz system bus)
 CPU MHz: 2666
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip (per chip), shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 2048MB ECC FB-DIMM DDR2-667
 Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
 Other Hardware:

Software

Operating System: Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T
 Compiler: Intel C++ 9.1 for EM64T build 20060323 and Fortran Compiler 9.1 for EM64T build 20060323
 File System: ext3
 System State: Runlevel 3

Notes/Tuning Information

GENERAL

ONESTEP=yes for all benchmarks
 +FDO : PASS1= -prof_gen PASS2= -prof_use

PORTABILITY FLAGS

-DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran

BASE TUNING

Baseline optimizations for C and Fortran: -fast +FDO

PEAK TUNING

basepeak=yes set for all benchmarks