



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter HS21 (2.33 GHz Xeon 5140, 4MB L2 Cache)

SPECint2000 = --

SPECint_base2000 = 2395

SPEC license #: 11 | Tested by: IBM Corporation | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	96.8	1446			
175.vpr	1400	80.2	1746			
176.gcc	1100	46.0	2390			
181.mcf	1800	47.4	3796			
186.crafty	1000	46.1	2167			
197.parser	1800	99.6	1807			
252.eon	1300	42.7	3043			
253.perlbmk	1800	62.8	2866			
254.gap	1100	47.6	2313			
255.vortex	1900	46.8	4060			
256.bzip2	1500	83.3	1801			
300.twolf	3000	112	2686			

Hardware

CPU: Intel Xeon processor 5140 (2.33 GHz, 1333 MHz bus)
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1, 2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 4096KB(I+D) on chip (per chip)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024 MB ECC PC2-5300F
 Disk Subsystem: 73GB SAS 15K RPM
 Other Hardware: Memory and I/O Expansion Unit (P/N 42C1600)

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
 Compiler: Intel C++ Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```