



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3400 (1.60 GHz Xeon 5110, 4MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 55.4

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	92.8	80.0			
171.swim	4	339	42.5			
172.mgrid	4	218	38.3			
173.applu	4	245	39.8			
177.mesa	4	93.7	69.3			
178.galgel	4	95.6	141			
179.art	4	82.6	146			
183.quake	4	115	52.2			
187.facerec	4	136	65.1			
188.amp	4	224	45.7			
189.lucas	4	220	42.1			
191.fma3d	4	225	43.3			
200.sixtrack	4	175	29.2			
301.apsi	4	285	42.3			

Hardware

CPU: Intel Xeon processor 5110 (1.60 GHz, 1333 MHz bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 4096KB(I+D) on chip (per chip)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1024 MB ECC PC2-5300F
Disk Subsystem: 80GB SATA 10K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
```