



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3650 (2.66 GHz Xeon 5150, 4MB L2 Cache)

SPECint_rate2000 = --

SPECint_rate_base2000 = 111

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
250	200	150	100	164.gzip	4	87.2	74.5			
				175.vpr	4	82.1	79.1			
				176.gcc	4	45.8	111			
				181.mcf	4	84.9	98.4			
				186.crafty	4	40.4	115			
				197.parser	4	96.1	86.9			
				252.eon	4	37.4	161			
				253.perlbnk	4	57.9	144			
				254.gap	4	48.2	106			
				255.vortex	4	48.0	184			
				256.bzip2	4	86.2	80.7			
				300.twolf	4	98.0	142			

Hardware

CPU: Intel Xeon processor 5150 (2.66 GHz, 1333 MHz bus)
CPU MHz: 2667
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 4096KB(I+D) on chip (per chip)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1024 MB ECC PC2-5300F
Disk Subsystem: 73GB SAS 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```