



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Intel(R) Corporation

Intel(R) DG965WH motherboard( 3.73 GHz, Intel(R) Pentium(R) Extreme processor 965)

SPECint\_rate2000 = 45.8

SPECint\_rate\_base2000 = 45.7

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	170	38.3	4	170	38.2
175.vpr	4	217	29.9	4	211	30.8
176.gcc	4	86.3	59.1	4	86.3	59.1
181.mcf	4	220	38.0	4	220	38.0
186.crafty	4	141	33.0	4	141	32.8
197.parser	4	209	39.9	4	207	40.3
252.eon	4	96.7	62.4	4	96.5	62.5
253.perlbnk	4	173	48.2	4	173	48.4
254.gap	4	99.6	51.3	4	99.6	51.3
255.vortex	4	119	74.0	4	119	74.0
256.bzip2	4	170	40.8	4	170	41.0
300.twolf	4	264	52.7	4	265	52.5

### Hardware

CPU: Intel(R) Pentium(R) Extreme processor 965( 3.73 GHz, 1066 MHz bus)  
CPU MHz: 3733  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12k micro-opsI + 16KBD per core, on chip  
Secondary Cache: 2MB(I+D) per core, on chip  
L3 Cache: None  
Other Cache: None  
Memory: 2 GB (2 1GB Corsair TWIN2X2048-8500C5 DDR2 1066 CL5-5-5 DIMMs)  
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)  
Other Hardware: ATI Radeon X1900 XTX PCI express graphics card

### Software

Operating System: Windows XP Professional SP2  
Compiler: Intel C++ Compiler 9.1 for 32-bit applications  
Build 20060323Z Package ID: W\_CC\_P\_9.1.020  
Microsoft Visual Studio 2005(for libraries)  
SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M-80.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Intel(R) Corporation**

Intel(R) DG965WH motherboard( 3.73 GHz, Intel(R) Pentium(R) Extreme processor 965)

SPECint\_rate2000 = 45.8

SPECint\_rate\_base2000 = 45.7

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M-80.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 07/2006

<http://www.intel.com/products/motherboard/dg965wh/index.htm>

The system bus runs at 1066 MHz