



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant BL460c (1.60 GHz, Intel Xeon processor 5110)

SPECfp2000 = **1910**  
SPECfp\_base2000 = **1753**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	56.2	2845	56.2	2845	
171.swim	3100	136	2281	131	2369	
172.mgrid	1800	156	1154	116	1547	
173.applu	2100	140	1503	112	1868	
177.mesa	1400	82.9	1689	76.2	1838	
178.galgel	2900	76.3	3799	76.3	3799	
179.art	2600	40.3	6449	40.3	6449	
183.quake	1300	74.3	1750	60.6	2145	
187.facerec	1900	103	1836	75.3	2522	
188.amp	2200	182	1208	182	1208	
189.lucas	2000	129	1554	128	1567	
191.fma3d	2100	153	1376	153	1376	
200.sixtrack	1100	180	611	180	611	
301.apsi	2600	238	1094	228	1140	

### Hardware

CPU: Intel Xeon processor 5110 (1.60 GHz, 4 MB L2 shared, 1066 MHz bus)  
CPU MHz: 1600  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 4 MB I+D on chip per chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 16 GB (8x2048 MB PC2-5300F)  
Disk Subsystem: 2x36 GB 10 K SAS  
Other Hardware:

### Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD64/EM64T, Update 3 Kernel 2.6.9-34.EL  
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
File System: ext2  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL460c (1.60 GHz, Intel Xeon processor 5110)

SPECfp2000 = 1910  
SPECfp\_base2000 = 1753

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

```
177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.quake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
188.ammamp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
```

### BIOS Configuration Notes

Power Regulator set to Static High Performance Mode

### Other Configuration Notes

Single processor kernel used