



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System X 3655 (AMD Opteron (TM) 2216)

SPECint2000 = **1662**
SPECint_base2000 = **1489**

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	95.6	1465	95.7	1463	
175.vpr	1400	120	1166	115	1218	
176.gcc	1100	65.8	1673	66.0	1667	
181.mcf	1800	267	673	161	1115	
186.crafty	1000	48.1	2078	48.1	2079	
197.parser	1800	162	1114	131	1371	
252.eon	1300	51.0	2548	45.7	2844	
253.perlbmk	1800	113	1595	99.9	1802	
254.gap	1100	69.9	1573	69.9	1573	
255.vortex	1900	81.5	2331	75.7	2510	
256.bzip2	1500	110	1366	110	1366	
300.twolf	3000	229	1309	177	1697	

Hardware

CPU: AMD Opteron 2216
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB (I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2GB, PC2-5300
 Disk Subsystem: SAS, 73GB 15K RPM
 Other Hardware: None

Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp
 Compiler: PathScale EKO Compiler Suite, Release 2.4
 PathScale EKOPATH(TM) Compiler Suite, Release 2.4
 File System: Linux/reiserfs
 System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
 C++ programs: -Ofast +FDO

Portability Flags:

186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST
 253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
 -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64

Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System X 3655 (AMD Opteron (TM) 2216)

SPECint2000 = 1662
SPECint_base2000 = 1489

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

```

186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
        -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
        -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
        -fno-math-errno -IPA:plimit=10000 +FDO
254.gap: basepeak = true
255.vortex: -Ofast -OPT:goto=off -CG:p2align=on
        -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2: basepeak = true
300.twolf: -O2 -CG:gcm=off:p2align_freq=100000
        -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
        -WOPT:mem_opnds=on -m32 +FDO

```