



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 G2 (AMD Opteron (TM) 2218)

SPECint_rate2000 = 42.4
SPECint_rate_base2000 = 39.3

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Sep-2006 Software Avail: Apr-2006

| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|-------------|-------------|--------------|------------|--------|---------|-------|
| 164.gzip | 2 | 97.1 | 33.4 | 2 | 97.1 | 33.4 |
| 175.vpr | 2 | 103 | 31.6 | 2 | 101 | 32.0 |
| 176.gcc | 2 | 56.3 | 45.4 | 2 | 57.3 | 44.6 |
| 181.mcf | 2 | 180 | 23.2 | 2 | 146 | 28.6 |
| 186.crafty | 2 | 58.7 | 39.5 | 2 | 52.2 | 44.5 |
| 197.parser | 2 | 111 | 37.5 | 2 | 112 | 37.1 |
| 252.eon | 2 | 52.2 | 57.8 | 2 | 39.7 | 76.0 |
| 253.perlbnk | 2 | 94.0 | 44.4 | 2 | 94.0 | 44.4 |
| 254.gap | 2 | 59.2 | 43.1 | 2 | 59.2 | 43.1 |
| 255.vortex | 2 | 72.4 | 60.9 | 2 | 65.8 | 67.0 |
| 256.bzip2 | 2 | 114 | 30.5 | 2 | 110 | 31.5 |
| 300.twolf | 2 | 172 | 40.4 | 2 | 142 | 48.9 |

Hardware

CPU: AMD Opteron (TM) 2218
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 GB (4x2048 MB PC2-5300P CL5.0)
 Disk Subsystem: 1x36 GB 10 K SAS
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
 Compiler: Intel C++ Compiler for 32-bit applications, (version 9.1 Build 20060323Z)
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -Qcxx_features -arch:SSE2 +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -O3 -Qipo -QaxN +FDO ONESTEP=yes shlw32M.lib
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 G2 (AMD Opteron (TM) 2218)

SPECint_rate2000 = 42.4
SPECint_rate_base2000 = 39.3

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Apr-2006

Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
            -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
256.bzip2:  -O3 -Qipo -QaxN -Qunroll2 shlw32M.lib
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

BIOS Configuration Notes
Node Interleaving Disabled
Other Configuration Notes