



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX150 S5, Intel Pentium D processor 925, 3.0 GHz

SPECint_rate2000 = 34.7

SPECint_rate_base2000 = 34.7

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	135	24.0	2	135	24.0
175.vpr	2	136	23.9	2	136	23.9
176.gcc	2	60.6	42.1	2	60.6	42.1
181.mcf	2	109	38.4	2	109	38.4
186.crafy	2	88.0	26.4	2	88.0	26.4
197.parser	2	141	29.6	2	141	29.6
252.eon	2	63.7	47.3	2	63.7	47.3
253.perlbnk	2	97.4	42.9	2	97.4	42.9
254.gap	2	68.5	37.3	2	68.5	37.3
255.vortex	2	74.1	59.5	2	74.1	59.5
256.bzip2	2	132	26.3	2	132	26.3
300.twolf	2	193	36.1	2	193	36.1

Hardware

CPU: Intel Pentium D processor 925 (3.0 GHz, 2x2MB L2, 800 MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops(I) + 16KB(D) on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2GB DDRII-RAM PC2-4200E (CAS 4-4-4)
Disk Subsystem: Western Digital (SATA, 7.2krpm, 160GB)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060323Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32M.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX150 S5, Intel Pentium D processor 925, 3.0 GHz

SPECint_rate2000 = 34.7

SPECint_rate_base2000 = 34.7

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>