



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel D945GPM motherboard(3.0 GHz, Intel (R) Pentium (TM) 4 processor 631)

SPECint2000 = 1456

SPECint_base2000 = 1456

SPEC license #: 13 Tested by: Intel(R) Corporation Test date: Jul-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	140	998	140	999	
175.vpr	1400	140	997	139	1009	
176.gcc	1100	65.4	1683	65.4	1683	
181.mcf	1800	103	1747	103	1747	
186.crafty	1000	91.0	1099	91.7	1091	
197.parser	1800	157	1147	156	1151	
252.eon	1300	65.6	1982	65.9	1973	
253.perlbmk	1800	103	1753	103	1753	
254.gap	1100	66.3	1658	66.3	1658	
255.vortex	1900	73.5	2583	73.5	2583	
256.bzip2	1500	136	1104	136	1102	
300.twolf	3000	201	1493	201	1491	

Hardware

CPU: Intel (R) Pentium (TM) 4 processor 631(3.0 GHz, 800 MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2MB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2 GB (2 1GB Micron DDR2 667 CL5-5-5 DIMMs)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: ATI Radeon X850 XT PCI express graphics card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M-80.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel D945GPM motherboard(3.0 GHz, Intel (R) Pentium (TM) 4 processor 631)

SPECint2000 = 1456

SPECint_base2000 = 1456

SPEC license #: 13 | Tested by: Intel(R) Corporation | Test date: Jul-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M-80.lib

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 07/2006:

<http://www.intel.com/products/motherboard/d945gpm/index.htm>

The system bus runs at 800 MHz