



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Rackable Systems
C1000-L03-25W30 (Intel Xeon 5160)

SPECfp2000 = **2773**

SPECfp_base2000 = **2773**

SPEC license #: 64 Tested by: Rackable Systems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	39.0	4103	39.0	4103	
171.swim	3100	109	2855	109	2855	
172.mgrid	1800	92.6	1943	92.6	1943	
173.applu	2100	97.1	2163	97.1	2163	
177.mesa	1400	45.3	3089	45.3	3089	
178.galgel	2900	42.5	6819	42.5	6819	
179.art	2600	22.3	11659	22.3	11659	
183.quake	1300	56.0	2323	56.0	2323	
187.facerec	1900	62.4	3044	62.4	3044	
188.amp	2200	101	2169	101	2169	
189.lucas	2000	96.1	2081	96.1	2081	
191.fma3d	2100	97.7	2150	97.7	2150	
200.sixtrack	1100	96.1	1145	96.1	1145	
301.apsi	2600	155	1674	155	1674	

Hardware

CPU: Intel(R) Xeon(R) CPU 5160 @ 3.0GHz
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chip(s)
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip, per chip, shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 1024MB ECC FB-DIMM DDR2-667MHz
 Disk Subsystem: 1 x 250GB SATA HDD
 Other Hardware:

Software

Operating System: Red Hat Enterprise Linux 4 ES Update 2 EM64T
 Compiler: Intel C++ 9.1.038 and Fortran Compiler 9.1.032 for EM64T
 File System: ext3
 System State: Runlevel 3

Notes/Tuning Information

-DSPEC_CPU2000_LP64 applied to all benchmarks
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL -DSPEC_CPU2000_GLIBC22
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
 -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
 178.galgel: -FI for fixed-format Fortran
 Portability for integer benchmarks
 Optimization flags
 ONESTEP=yes for all benchmarks
 +FDO implies feedback-directed optimization PASS1: -prof_gen PAS2: -prof_use
 Baseline optimizations for C: -fast -auto_ilp32 +FDO
 Baseline optimizations for C++: -fast -auto_ilp32 +FDO
 basepeak=yes set for all benchmarks
 Portability for fp benchmarks
 Optimization flags
 ONESTEP=yes for all benchmarks



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Rackable Systems
C1000-L03-25W30 (Intel Xeon 5160)

SPECfp2000 = 2773

SPECfp_base2000 = 2773

SPEC license #: 64 Tested by: Rackable Systems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Notes/Tuning Information (Continued)

+FDO implies feedback-directed optimization PASS1: -prof_gen PAS2: -prof_use
Baseline optimizations for C and Fortran: -fast +FDO
basepeak=yes set for all benchmarks
Taskset utility used to bind process to CPU(s)