



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX150 S5, Intel Xeon processor 3050, 2.13 GHz

SPECfp_rate2000 = 37.7

SPECfp_rate_base2000 = 37.7

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	58.6	63.3	2	58.6	63.3
171.swim	2	222	32.4	2	222	32.4
172.mgrid	2	153	27.3	2	153	27.3
173.applu	2	174	28.1	2	174	28.1
177.mesa	2	62.0	52.4	2	62.0	52.4
178.galgel	2	109	61.7	2	109	61.7
179.art	2	92.7	65.1	2	92.7	65.1
183.quake	2	83.3	36.2	2	83.3	36.2
187.facerec	2	95.3	46.3	2	95.3	46.3
188.amp	2	168	30.4	2	168	30.4
189.lucas	2	137	34.0	2	137	34.0
191.fma3d	2	154	31.6	2	154	31.6
200.sixtrack	2	138	18.5	2	138	18.5
301.apsi	2	174	34.6	2	174	34.6

Hardware

CPU: Intel Xeon processor 3050 (2.13 GHz, 2MB L2, 1066 MHz system bus)
CPU MHz: 2133
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1 chip
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2GB DDRII-RAM PC2-4200E (CAS 4-4-4)
Disk Subsystem: Western Digital (SATA, 7.2krpm, 160GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10
Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: reiserfs
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX150 S5, Intel Xeon processor 3050, 2.13 GHz

SPECfp_rate2000 = 37.7

SPECfp_rate_base2000 = 37.7

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1066 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS configuration:

Adjacent Sector Prefetch = disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>