



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX600 S3, Intel Xeon processor 7110M, 2.60 GHz

SPECfp_rate2000 = 54.2

SPECfp_rate_base2000 = 54.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Feb-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	161	92.3	8	161	92.3
171.swim	8	557	51.7	8	557	51.7
172.mgrid	8	377	44.3	8	377	44.3
173.applu	8	439	44.4	8	439	44.4
177.mesa	8	218	59.5	8	218	59.5
178.galgel	8	320	84.1	8	320	84.1
179.art	8	243	99.5	8	243	99.5
183.quake	8	251	48.0	8	251	48.0
187.facerec	8	280	63.0	8	280	63.0
188.amp	8	541	37.7	8	541	37.7
189.lucas	8	384	48.3	8	384	48.3
191.fma3d	8	408	47.8	8	408	47.8
200.sixtrack	8	343	29.7	8	343	29.7
301.apsi	8	472	51.1	8	472	51.1

Hardware

CPU: Intel Xeon processor 7110M (2.60 GHz, 2x1MB L2, 4MB L3, 800 MHz system bus)
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2,4 chips
Parallel: No
Primary Cache: 12k micro-ops(I) + 16KB(D) on chip, per core
Secondary Cache: 1024KB(I+D) on chip, per core
L3 Cache: 4MB on chip, per chip
Other Cache: N/A
Memory: 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)
Disk Subsystem: Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext3
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX600 S3, Intel Xeon processor 7110M, 2.60 GHz

SPECfp_rate2000 = 54.2

SPECfp_rate_base2000 = 54.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Feb-2006

Notes/Tuning Information (Continued)

The system bus runs at 800 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

This result was measured on the PRIMERGY TX600 S3. The PRIMERGY TX600 S3 and the PRIMERGY RX600 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>