



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL585 G2 (AMD Opteron (TM) 8220SE)

SPECint_rate2000 = **86.1**
SPECint_rate_base2000 = **76.9**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Sep-2006 Software Avail: Jul-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	82.0	79.2	4	81.9	79.3
175.vpr	4	109	59.7	4	104	62.4
176.gcc	4	58.0	88.1	4	58.7	87.0
181.mcf	4	292	28.6	4	175	47.7
186.crafty	4	41.0	113	4	41.0	113
197.parser	4	142	58.8	4	112	74.7
252.eon	4	43.5	139	4	38.7	156
253.perlbnk	4	97.9	85.3	4	86.3	96.8
254.gap	4	64.0	79.8	4	62.8	81.2
255.vortex	4	71.2	124	4	67.1	131
256.bzip2	4	99.9	69.7	4	99.9	69.7
300.twolf	4	212	65.8	4	162	85.7

Hardware

CPU: AMD Opteron (TM) 8220SE
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 2,4 chips
Parallel: No
Primary Cache: 64 KB I + 64 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16 GB (8x2 GB PC2-5300P CL5)
Disk Subsystem: 1x36.4 GB 10 K SAS
Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 3
SuSE kernel 2.6.5-7.244-smp
Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.4
File System: Linux/ext2
System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -Ofast +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LP64
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
-DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
255.vortex: -DSPEC_CPU2000_LP64
Peak tuning:
164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
175.vpr: -O3 -ipa -m32 +FDO
176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
-OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL585 G2 (AMD Opteron (TM) 8220SE)

SPECint_rate2000 = 86.1
SPECint_rate_base2000 = 76.9

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Jul-2006

Notes/Tuning Information (Continued)

```
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```

BIOS Configuration Notes

Node Interleaving Disabled

Other Configuration Notes

Taskset utility used to bind process to CPU(s)