



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Acer Incorporated

Acer Altos R520 (3.73 GHz Intel Xeon Processor 5080)

SPECint\_rate2000 = 80.6

SPECint\_rate\_base2000 = 80.5

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2006 | Hardware Avail: Nov-2006 | Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	172	75.4	8	172	75.4
175.vpr	8	261	49.9	8	254	51.1
176.gcc	8	89.8	114	8	89.8	114
181.mcf	8	420	39.8	8	420	39.8
186.crafty	8	143	64.7	8	143	64.7
197.parser	8	204	82.0	8	202	82.7
252.eon	8	111	109	8	112	108
253.perlbnk	8	177	94.5	8	177	94.4
254.gap	8	114	89.8	8	114	89.8
255.vortex	8	134	132	8	134	132
256.bzip2	8	211	66.0	8	211	66.1
300.twolf	8	274	102	8	275	101

### Hardware

CPU: Intel Xeon Processor 5080 (3.73 GHz, 2x2MB L2, 1066MHz system bus)  
CPU MHz: 3733  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip, per core  
Secondary Cache: 2048KB(I+D) on chip, per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8 x 2048MB ECC FB-DIMM 667  
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD  
Other Hardware:

### Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790), Service Pack 1  
Compiler: Intel C++ Compiler 9.0 Build 20051130Z for IA32  
Microsoft Visual Studio .Net 2003 (7.1.3091, for libraries)  
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: -fast -Oa -Qunroll1 +FDO
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Acer Incorporated**

Acer Altos R520 (3.73 GHz Intel Xeon Processor 5080)

SPECint\_rate2000 = 80.6

SPECint\_rate\_base2000 = 80.5

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2006 | Hardware Avail: Nov-2006 | Software Avail: Nov-2005

## Notes/Tuning Information (Continued)

300.twolf: -fast +FDO shlw32M.lib

Enable hardware prefetching and adjacent cache line prefetch BIOS setting

This result was measured on the Acer Alto R720.

The Altos R520 and Altos R720 are electronically equivalent.