



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 575 (1900 Mhz, 16 CPU, SLES)

SPECfp_rate2000 = 541
SPECfp_rate_base2000 = 478

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Feb-2006 | Software Avail: Dec-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	32	87.1	682	32	79.2	750
171.swim	32	207	555	32	176	656
172.mgrid	32	177	378	32	145	460
173.applu	32	223	350	32	186	419
177.mesa	32	174	299	32	174	299
178.galgel	32	137	783	32	110	976
179.art	32	44.6	2165	32	41.8	2310
183.equake	32	56.3	857	32	42.4	1139
187.facerec	32	129	549	32	129	549
188.amp	32	313	261	32	317	258
189.lucas	32	155	479	32	110	675
191.fma3d	32	230	339	32	217	360
200.sixtrack	32	223	183	32	200	204
301.apsi	32	272	355	32	270	357

Hardware	Software
CPU: POWER5+ CPU MHz: 1900 FPU: Integrated CPU(s) enabled: 16 cores, 8 chips, 2 cores/chip (SMT on) CPU(s) orderable: 8,16 core Parallel: No Primary Cache: 64 KB I + 32 KB D on chip per core Secondary Cache: 1920 KB I+D on chip per chip L3 Cache: 36 MB unified off chip per chip Other Cache: None Memory: 64 GB (32x2GB) Disk Subsystem: 1x73GB SCSI, 15K RPM Other Hardware:	Operating System: SLES SUSE Linux Enterprise Server 10 (ppc) VERSION = 10 w/2.6.16.21-0.8-ppc64 Linux kernel Compiler: IBM XL C/C++ Advanced Edition V8.0.1 for Linux IBM XL Fortran Advanced Edition V10.1.1 for Linux Other software: - IBM Engineering and Scientific Subroutine Library (ESSL) for Linux - Version 4.2.5 File System: reiserfs System State: Multi-User

Notes/Tuning Information

+FDO
 Feedback directed optimization enabled by: PASS1=-qpdf1 PASS2=-qpdf2

FP compilers
 C: invoked as xlc
 Fortran 77 and Fortran 90: invoked as xlf90, except as noted below

FP Portability Flags
 -qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu,
 178.galgel, 200.sixtrack, 301.apsi
 -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

FP Base Optimization Flags:
 C: +FDO -O5
 Fortran: +FDO -O5



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 575 (1900 Mhz, 16 CPU, SLES)

SPECfp_rate2000 = 541
SPECfp_rate_base2000 = 478

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Feb-2006 | Software Avail: Dec-2006

Notes/Tuning Information (Continued)

Floating Point Peak Flags

```

168.wupwise
  +FDO -O5 -qsave -lmass
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
171.swim
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
172.mgrid
  +FDO -O4 -q64
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
173.applu
  +FDO -O5 -q64
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
177.mesa
  basepeak=1
178.galgel
  Fortran invoked as xlf90_r
  +FDO -O5 -qessl -lessl -lmass
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
179.art
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
183.quake
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
187.facerec
  basepeak=1
188.amp
  +FDO -O3 -qalign=linuxppc
189.lucas
  +FDO -O3 -qarch=auto -qtune=auto
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
191.fma3d
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
200.sixtrack
  +FDO -O3 -qarch=auto -qtune=auto
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
301.apsi
  Fortran invoked as xlf90_r
  +FDO -O5 -qessl
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
  extra_libs = -lessl

```

System Settings:
-- ulimit stack size set to unlimited

SMT: Acronym for 'Simultaneous Multi-Threading'. A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. SMT is enabled by default.

Large pages reserved as follows by root user:
echo 960 > /proc/sys/vm/nr_hugepages



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 575 (1900 Mhz, 16 CPU, SLES)

SPECfp_rate2000 = 541

SPECfp_rate_base2000 = 478

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Feb-2006 | Software Avail: Dec-2006

Notes/Tuning Information (Continued)

System configured with libhugetlbfs library for application access to large pages
Environment variables set as follows:
export HUGETLB_MORECORE=yes

Each process was bound to a cpu using submit= with the taskset command
submit = taskset -p -c \\${SPECUSERNUM} \\$\\$ >/dev/null ; \$command