



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec MX221 (Intel Xeon 5160 processor, 3.00GHz)

SPECfp_rate2000 = 81.5

SPECfp_rate_base2000 = 81.5

SPEC license #: 9001 | Tested by: Itaotec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	68.0	109	4	68.0	109
171.swim	4	263	54.8	4	263	54.8
172.mgrid	4	165	50.5	4	165	50.5
173.applu	4	184	52.8	4	184	52.8
177.mesa	4	52.2	125	4	52.2	125
178.galgel	4	57.9	233	4	57.9	233
179.art	4	58.9	205	4	58.9	205
183.equake	4	84.6	71.3	4	84.6	71.3
187.facerec	4	89.0	99.0	4	89.0	99.0
188.amp	4	145	70.5	4	145	70.5
189.lucas	4	172	54.1	4	172	54.1
191.fma3d	4	157	62.1	4	157	62.1
200.sixtrack	4	94.2	54.2	4	94.2	54.2
301.apsi	4	182	66.2	4	182	66.2

Hardware

CPU: Intel Xeon 5160 processor (3.00 GHz, 4MB L2 shared, 1333 MHz system bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4096KB(I+D) on chip, per chip, shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)ECC
 Disk Subsystem: 1 x 36GB U320 SCSI 10000 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
 Compiler: Intel C++ Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Intel Fortran Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Microsoft Visual Studio .NET 7.0.9466 (for libraries),
 MicroQuill SmartHeap for SMP Library 8.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO

for C programs: -fast +FDO shlSMPMt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>