



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec MX221 (Intel Xeon 5160 processor, 3.00GHz)

SPECint_rate2000 = 120

SPECint_rate_base2000 = 120

SPEC license #: 9001 | Tested by: Itaotec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	77.7	83.6	4	77.7	83.6
175.vpr	4	78.0	83.2	4	78.0	83.2
176.gcc	4	42.4	120	4	42.4	120
181.mcf	4	91.3	91.5	4	91.3	91.5
186.crafy	4	36.3	128	4	36.3	128
197.parser	4	81.6	102	4	81.6	102
252.eon	4	33.6	180	4	33.6	180
253.perlbnk	4	54.0	155	4	54.0	155
254.gap	4	45.0	113	4	45.0	113
255.vortex	4	44.4	199	4	44.4	199
256.bzip2	4	78.8	88.3	4	78.8	88.3
300.twolf	4	87.9	158	4	87.9	158

Hardware

CPU: Intel Xeon 5160 processor (3.00 GHz, 4MB L2 shared, 1333 MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4096KB(I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)ECC
Disk Subsystem: 1 x 36GB U320 SCSI 10000 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio .NET 7.0.9466 (for libraries),
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

```
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

```
for C programs: -fast -QxP +FDO sh1SMPMt.lib
for C++ programs: -fast -Qcxx_features +FDO
```

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>