



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Acer Incorporated**  
Acer Altos G540 (2.66 GHz Intel Xeon Processor 5150)

SPECfp\_rate2000 = 43.6  
SPECfp\_rate\_base2000 = 43.6

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Oct-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	53.8	69.0	2	53.8	69.0
171.swim	2	224	32.1	2	224	32.1
172.mgrid	2	160	26.1	2	160	26.1
173.applu	2	171	28.6	2	171	28.6
177.mesa	2	50.0	65.0	2	50.0	65.0
178.galgel	2	62.2	108	2	62.2	108
179.art	2	46.9	129	2	46.9	129
183.equake	2	105	28.8	2	105	28.8
187.facerec	2	79.3	55.6	2	79.3	55.6
188.amp	2	126	40.7	2	126	40.7
189.lucas	2	129	35.9	2	129	35.9
191.fma3d	2	142	34.3	2	142	34.3
200.sixtrack	2	110	23.2	2	110	23.2
301.apsi	2	187	32.2	2	187	32.2

### Hardware

CPU: Intel Xeon Processor 5150 (2.66 GHz, 4MB L2, 1333MHz system bus)  
CPU MHz: 2666  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 4096KB(I+D) on chip (per chip), shared  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8 x 1024MB ECC FB-DIMM DDR2-667  
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD  
Other Hardware:

### Software

Operating System: Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T  
Compiler: Intel C++ 9.1 for EM64T build 20060323 and Fortran Compiler 9.1 for EM64T build 20060323  
File System: ext3  
System State: Runlevel 3

## Notes/Tuning Information

### GENERAL

ONESTEP=yes for all benchmarks  
+FDO : PASS1= -prof\_gen PASS2= -prof\_use

### PORTABILITY FLAGS

-DSPEC\_CPU2000\_LP64 applied to all benchmarks  
178.galgel: -FI for fixed-format Fortran

### BASE TUNING

Baseline optimizations for C and Fortran: -fast +FDO

### PEAK TUNING

basepeak=yes set for all benchmarks