



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**IBM Corporation**  
IBM System X 3655 (AMD Opteron (TM) 2218)

SPECint\_rate2000 = 40.8  
SPECint\_rate\_base2000 = 36.6

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Oct-2006 | Hardware Avail: Oct-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	88.5	36.7	2	88.6	36.7
175.vpr	2	114	28.6	2	110	29.7
176.gcc	2	61.7	41.4	2	61.4	41.5
181.mcf	2	282	14.8	2	171	24.5
186.crafty	2	44.5	52.1	2	44.5	52.1
197.parser	2	149	27.9	2	119	35.1
252.eon	2	47.2	63.9	2	42.4	71.2
253.perlbnmk	2	104	40.0	2	92.2	45.3
254.gap	2	66.7	38.2	2	66.7	38.2
255.vortex	2	75.8	58.2	2	70.5	62.5
256.bzip2	2	104	33.6	2	104	33.6
300.twolf	2	218	31.9	2	169	41.1

### Hardware

CPU: AMD Opteron 2218  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB (I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8x2GB, PC2-5300  
 Disk Subsystem: SATA, 80GB 10K RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp  
 Compiler: PathScale EKO Compiler Suite, Release 2.4  
 PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
 File System: Linux/reiserfs  
 System State: Multi-user, run level 3

## Notes/Tuning Information

+FDO: PASS1= -fb\_create fbdata PASS2= -fb\_opt fbdata

### Baseline optimization flags:

C programs: -Ofast +FDO  
 C++ programs: -Ofast +FDO

### Portability Flags:

186.crafty: -DLINUX\_i386  
 252.eon: -DHAS\_ERRLIST  
 253.perlbnmk: -DSPEC\_CPU2000\_LINUX\_I386 -DSPEC\_CPU2000\_NEED\_BOOL  
 -DSPEC\_CPU2000\_GLIBC22 -DSPEC\_CPU2000\_LP64  
 254.gap: -DSYS\_IS\_USG -DSYS\_HAS\_IOCTL\_PROTO -DSYS\_HAS\_TIME\_PROTO  
 -DSYS\_HAS\_CALLOC\_PROTO -DSPEC\_CPU2000\_LP64  
 255.vortex: -DSPEC\_CPU2000\_LP64

### Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll\_size=0 +FDO  
 175.vpr: -O3 -ipa -m32 +FDO  
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO  
 181.mcf: -O3 -ipa -IPA:field\_reorder=on -m32 +FDO



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3655 (AMD Opteron (TM) 2218)

SPECint\_rate2000 = 40.8

SPECint\_rate\_base2000 = 36.6

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Oct-2006 | Hardware Avail: Oct-2006 | Software Avail: Mar-2006

## Notes/Tuning Information (Continued)

```
186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
        -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
        -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
        -fno-math-errno -IPA:plimit=10000 +FDO
254.gap: basepeak = true
255.vortex: -Ofast -OPT:goto=off -CG:p2align=on
        -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2: basepeak = true
300.twolf: -O2 -CG:gcm=off:p2align_freq=100000
        -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
        -WOPT:mem_opnds=on -m32 +FDO
```