



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3550 (1.6 GHz Xeon 5110, 4MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 32.4

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	72.7	51.0			
171.swim	2	238	30.2			
172.mgrid	2	188	22.2			
173.applu	2	210	23.3			
177.mesa	2	90.0	36.1			
178.galgel	2	90.0	74.7			
179.art	2	69.5	86.8			
183.quake	2	83.5	36.1			
187.facerec	2	122	36.0			
188.amp	2	215	23.7			
189.lucas	2	151	30.6			
191.fma3d	2	197	24.7			
200.sixtrack	2	174	14.6			
301.apsi	2	272	22.2			

Hardware

CPU: Intel Xeon processor 5110 (1.6 GHz, 1066 MHz bus)
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1, 2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 4096KB(I+D) on chip (per chip)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024 MB ECC PC2-5300F
 Disk Subsystem: 73GB SAS 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```